



# PURA-FIT®

**6800 without cord**

**6900 with cord**

*Tapered for easier insertion.*

*Improved, softer foam for maximum comfort.*

*Hygienically packaged in biodegradable paper pouches.*

*Non-irritating, smooth surface.*

*NRR 31. High rating.*

*Longer length for easy fitting and removal.*

*Brightly colored for easy compliance checks.*

*Model 6900 has cord securely and cleanly attached.*



## **FIT TO BE TRIED.**

Pura-Fit® earplugs are tapered so they are easier to insert in any size ear canal. And they are longer too, so they are easier to grasp.

## **MORE COMFORT, LESS COMPLAINING.**

Pura-Fit® is designed for more compliance and fewer complaints. The special foam is formulated for softness and comfort, and the outer surface is smooth, so it does not irritate worker's ears.

## **NRR 31. ONE OF THE HIGHEST RATINGS AVAILABLE.**

Pura-Fit® is independently tested to ANSI S3.19-1974 by Dr. Paul Michael, Penn State University. So you know you're getting excellent protection against industrial noise.

## **MOLDEX TECHNICAL ASSISTANCE.**

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call 800/421-0668 or 310/837-6500 ext. 504.

**6800 without cord**  
**6900 with cord**

# PURA-FIT®

## MEAN ATTENUATION DATA OF PURA-FIT®

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Real Ear Attenuation (dB)	32.8	34.7	37.9	38.1	38.6	42.8	44.6	44.7	43.9
Standard Deviation (dB)	4.0	3.8	3.1	3.0	2.9	2.9	3.6	4.1	4.6

Tested to ANSI S.319-1974 by Dr. Paul Michael, Penn State.  
 EPA Noise Reduction Rating 31 decibels.

### WARNING

Use this laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending on how the protectors are fitted and worn.

Failure to follow all instructions could result in hearing loss or injury. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.

Pura-Fit must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.

Overprotection can be dangerous. The wearer must be able to hear warning signals.

Wearers with hearing loss should exercise extreme caution.

It is the employer's responsibility to ensure that the type of hearing protector and its NRR is appropriate for the user in their particular workplace.

Failure to follow these warnings could result in serious injury or death.

## TECHNICAL SERVICE

For technical assistance, information and training materials, call Moldex Technical Service Department, 800/421-0668 or 310/837-6500 ext. 504.

## PACKAGING

6800 without cord  
 1 Pair/Pouch  
 200 Pairs/Dispenser Box  
 10 Dispenser Boxes/Case  
 2000 Pairs/Case

6900 with cord  
 1 Pair/Polybag  
 100 Pairs/Dispenser Box  
 20 Dispenser Boxes/Case  
 2000 Pairs/Case

## LIMITED WARRANTY

### IMPORTANT NOTICE TO PURCHASER

This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied. There are no other warranties which extend beyond the description on the face hereof.

The physical standards and specifications of Moldex will be met by products sold. **Exclusive Remedies:** damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex products proved to be defectively manufactured. Except as provided above, Moldex shall not be liable or responsible for any loss, damages, or liability, direct, indirect, incidental, special or consequential, arising out of a sale, use or misuse, or the inability to use products by the user.

## DISTRIBUTED BY:



**MOLDEX-METRIC, INC.**  
 10111 W. Jefferson Blvd.  
 Culver City, CA 90232  
 800/421-0668 310/837-6500  
 FAX 310/837-9563  
 www.moldex.com e-mail: sales@moldex.com  
 Patents Pending  
 Made in the U.S.A. 9700-769 REV C 12/99



**In Canada:**  
 Moldex-Metric, Inc.  
 The Ralston/Cansafe Group  
 P.O. Box 263  
 Fergus, Ontario N1M 2W8  
 PHONE 800/267-1611 FAX 519/787-3732